

Key Features


- Versatile touch applications
- Efficient multitasking
- Touch annotation for presentations
- Accurate yet smooth touch experience
- Comfortable working angles & quickly start your work



Product Description

With responsive in-cell touch technology and an advanced ergonomic design, the ViewSonic® TD2455 touch monitor delivers hands-on control for more productive workspaces and collaborative classrooms. With high-performance in-cell touch technology, this 24" (23.8" viewable) Full HD display provides smooth and responsive touch tracking, along with amazing screen performance, within a sleek and bezelless design. USB Type-C connectivity offers a single-cable plug-and-play solution for laptops, while DisplayPort output enables easy screen mirroring or extended desktops ideal for office productivity and podium touch applications such as conference rooms or classrooms. A magnetic stylus pen lets you write or draw on screen, and easily attaches to the display stand for secure storage. So whether used on its own on office desktops, as a presentation station in corporate meeting spaces, or as a front-of-classroom interactive teaching hub, the TD2455 helps to boost efficiency and productivity. *Some laptops may need to enter BIOS mode and change the power management setting to "tap-to-wake".





datasheet_TD2455

		datasheet_TD2455	
DISPLAY		INPUT SIGNAL	
Display Size (in.):	24	Frequency Horizontal:	15 ~ 82KHz
Viewable Area (in.):	23.8	Frequency Vertical:	50 ~ 75Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	1920 x 1080	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet -
Resolution Type:	FHD	Digital Offici	Туре С
Static Contrast Ratio:	1,000:1 (typ)	ERGONOMICS	
Dynamic Contrast Ratio:	50M:1	Tilt (Forward/Back):	-5° / 60°
Light Source:	LED	WEIGHT (IMPERIAL)	
Brightness:	250 cd/m² (typ)	Net (lbs):	14.2
Colors:	16.7M	Net Without Stand (Ibs):	8.2
Color Space Support:	8 bit (6 bit + A-FRC)	Gross (Ibs):	18.6
Aspect Ratio:	16:9	WEIGHT (METRIC)	
Response Time (Typical GTG):	6ms	Net (kg):	6.4
Response Time (GTG w/OD):	6ms	Net Without Stand (kg):	3.7
Viewing Angles:	178º horizontal, 178º vertical	Gross (kg):	8.4
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (IMPERIAL) (W	•
Curvature:	Flat	Packaging (in.):	24.3 x 16.3 x 11.2
Refresh Rate (Hz):	60	Physical (in.):	21.2 x 16.8 x 11.3
Blue Light Filter:	Yes	Physical Without Stand (in.):	21.2 x 12.6 x 2
Flicker-Free:	Yes	DIMENSIONS (METRIC) (WX	•
Calar Comuti	NTSC: 72% size (Typ), sRGB: 102%	Packaging (mm):	617 x 415 x 285
Color Gamut:	size (Typ)	Physical (mm):	539 x 426 x 286
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Physical Without Stand (mm):	539 x 320 x 52
Touch Screen:	Projected Capacitive, 10-point multi- touch	GENERAL	
Surface Treatment:	Anti-Glare, Hard Coating (3H)		cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Bronze, CEC, MX-
	Anti-Olare, Hard Coating (OT)	Regulations:	CoC, México Energy, CÉ, CE ÉMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, PSB, RCM, GEMS, CCC, China RoHS, China
PC Resolution (max):	1920x1080	rtogulationo.	
Mac® Resolution (max):	1920x1080		Energy Label, CECP
PC Operating System:	Windows 7/8.1/10 certified; macOS tested	PACKAGE CONTENTS:	TD2455 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB A/B Cable (v3.2 Male-Male) x1, Quick Start Guide x1 Passive touch pen x1, Passive touch
Mac® Resolution (min):	1920x1080		
CONNECTOR	102001000		pen head x1
USB 3.1 Type A:	1	Recycle/Disposal:	Please dispose of in accordance wit
USB 3.1 Type B:	1		local, state or federal laws.
USB 3.1 Type C:	1	Warranty:	*Warranty offered may differ from market to market
3.5mm Audio Out:	1	Power Management:	Energy Star standards, EPEAT
HDMI 1.4:	1		
Display Port:	1		
Display Port Out:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	9.7W		
Eco Mode (optimized):	12.8W		
Consumption (typical):	17.9W		
Consumption (typical).	20.4W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.3W		
Power Supply:	Internal		
ADDITIONAL HARDWARE	internal		
Kensington Lock Slot:	1		
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS	maye Aujust, setup mellu		
	32°E to 104°E (0°C to 40°C)		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing): WALL MOUNT	20% to 90%		
VERA Compatible:	400 400		

Copyright © ViewSonic Corporation 2000-2020. All rights reserved.

100 x 100 mm

VESA Compatible: